



Email: sales@coastalmarine.net.au

Website: www.coastalmarine.net.au/

178 Edith Street Innisfail QLD 4860



250 HP Fourstroke

POA

Specifications

Boat Details

Price POA Boat Brand Mercury
Model 250 HP Length 0.00

Year 2023 Category Boat Engines and Outboards

Hull Style Hull Type
Power Type Stock Number 0

Condition New State Queensland

Suburb INNISFAIL Engine Make

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: 07 4061 8272

Email: sales@coastalmarine.net.au

Website: www.coastalmarine.net.au/

178 Edith Street Innisfail QLD 4860

Description

The new Mercury 250hp FourStroke is precision engineered from skeg to cowl. Packed with advanced technology to improve all aspects of performance and reliability. the Robust 4.6 Litre V-8 engine is designed to minimise weight and maximise fuel economy. Delivering Mercury's best ever FourStroke hole shot, top speed and fuel efficiency. The 250hp FourStroke now comes with a 3+3=6 Year factory warranty.ENGINE DETAILS

Quick-revving double-overhead camshaft design and deep-breathing intake deliver thrilling and satisfying performance. Great for aluminum console, deck, inflatable rigid hull, inshore fishing, offshore fishing, and runabout boats and tritoons.SPECIFICATIONS - 250

HP / kW

• 250 / 186

Engine type

• V-8

MidSection

Conventional MidSection

Displacement (CID/CC)

• 279 CID

Displacement (L)

• 4.6L

Cylinder Configuration

• V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM

• 5200-6000

Air induction

• Performance-Tuned Long-Runner Intake Manifold

Fuel induction system

• Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt

• 85-amp (1071 Watt) with Idle Charge

Recommended fuel

• Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

• NMMA Certified FCW SAE 10W-30

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: 07 4061 8272

Email: sales@coastalmarine.net.au

Website: www.coastalmarine.net.au/

178 Edith Street Innisfail QLD 4860

Engine protection operator warning system

• SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

Yes

Starting

• Electric Start with SmartStart Protection

Controls

• Remote Mechanical or Digital Throttle & Shift (DTS)

Steering

- Big Tiller (optional)
- Hydraulic (standard)
- Power (optional)

Shaft length

- 20" / 508 mm
- 25" / 635 mm
- 30" / 762 mm

Gearcase ratio

• 1.75:1

Dry weight *Lightest model available

• 527 lbs / 239 kgs

CARB star rating

• 3

Bore and stroke

• 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition

• SmartCraft PCM 112 Digital Inductive

Cooling system

• Water-cooled with thermostat

Gear shift

• F-N-R

Gearcase options

• 5.44"

Trim system

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: 07 4061 8272

Email: sales@coastalmarine.net.au

Website: www.coastalmarine.net.au/

178 Edith Street Innisfail QLD 4860

Power trim and tilt

Exhaust system

• Through prop

Counter Rotation

Available

Color

- Cold Fusion White
- Pearl Fusion White
- Phantom Black
- Warm Fusion White

Lubrication system

• Integrated wet sump

Oil Capacity

• 7.0 Quarts / 6.6 Liters

Maximum Trim Range

• 20° (-6° to 14°)

Maximum Tilt Range

• 73° (-6° to 67°)

Engine Details

Displacement 4.6 Horse Power 250

Steering Big Tiller (optional), Hydraulic (standard), Power (optional)

Fuel Capacity 6.6

Disclaimer